



PRISM PAR VW

Specification Sheet



5 Holt Drive,
Stony Point, NY 10980
845-947-3034
info@tslight.com

Control

- Protocol: USITT DMX-512
- DMX Channels: 3/4 or 7-channel
- Input: 3/5-pin XLR Male
- Output: 3/5-pin XLR Female
- Standalone, Master/Slave, Sound Active, Color Preset

Power

- Voltage: 100-264VAC, 47-63 Hertz
- Power Consumption: TBA
- Max. Operating Temp.: 104 degrees F (40° C) ambient

Optics

- 18x 5W 3-in-1 A/C/W LEDs, 100,000 hours
- 25° beam angle

AnyFi™ Wireless DMX Receiver

- Frequency Hopping W-DMX™ Protocol
- 2.4Ghz ISM (2.402-2.48Ghz), 512 channels, 7 frequency groups
- Less Than 5ms Latency
- Receiver sensitivity: -94d

Main Features

- 18x 5W 3-in-1 A/C/W LEDs, 100,000 hours
- Built-in AnyFi™ wireless DMX receiver (user selectable 2.4Ghz or W-DMX™)
- Achieve white color temperatures from 2600k-7500k
- Natural convection cooled, totally silent operation
- User selectable 32-bit dimming curves
- Variable electronic dimmer strobe
- Built-in auto programs & sound active in standalone and M/S
- Color mixing ability in standalone mode
- 25 degree beam angle
- User selectable 3/4 or 7-channel DMX modes
- Flicker-free constant-current LED driver
- LED control panel with 4* touch sensitive buttons
- 3/5-pin male input and 3/5-pin female output
- PowerCon™ compatible AC power In/Out

Weight & Dimensions

- Dimensions: 10.7" (272.1 mm) x 5.7" (144 mm) x 11.2 inches (284.1 mm)
- Weight: 11.5 lbs. (5.2 kg)

Mounting Options

- MNB** Clamp for pipe up to 2" OD
- CM4** Canopy for mounting to J-box
- USI** Unistrut mount
- STA** Controltrac adapter (2x)

Ordering Matrix

Model	Finish	Mounting
CREW	B - Black W - White	See Options

Example: CREW-B-MNB

CREW-_____ - _____