



PRISM LINE 1

Specification Sheet



5 Holt Drive,
Stony Point, NY 10980
845-947-3034
info@tslight.com

Control

- Protocol: USITT DMX-512
- DMX Channels: 4/5/9 or 10-Channels
- Input: 3-pin XLR Male
- Output: 3-pin XLR Female
- Standalone, Master/Slave, Sound Active, Color Preset

Power

- Operating Voltage: 100-264VAC, 50-60 Hertz
- Fuse: 3.5A 250V
- Power Consumption: 290W, 3.66A, pf: .65
- Max. Operating Temp.: 104° F (40° C) ambient

Main Features

- 12x 25W 5-in-1 COB LEDs, 100,000 hours
- Variable electronic strobe
- Variable electronic dimmer
- Built-in color & chase macros via DMX
- Built-in automated programs + Sound Active via M/S
- RGBAW color mixing ability in standalone mode
- Beam Angle: 60 degree
- 3-pin male input and 3-pin female output
- User selectable 4/5/9 or 10-Channel DMX modes
- Flicker-free constant-current LED driver
- Easy to use LED control panel
- PowerCon™ compatible AC power In/Out connectors

Weight & Dimensions

- 35.3" (986 mm) x 3.4" (85 mm) x 9.3 inches (235 mm)
- Weight: 23.2 lbs (10.5 kg)

Photometric Data in LUX (RGBAW in Full)



15,660 @ 1m	5,700 @ 2m	2,600 @ 3m	1,420 @ 4m	1,000 @ 5m
-------------	------------	------------	------------	------------

Mounting Options

- MNB** Clamp for pipe up to 2" OD
CM4 Canopy for mounting to J-box
US1 Unistrut mount
STA Controltrac adapter (2x)

Ordering Matrix

Model	Array	Finish -	Mounting
HS5	RGBAW	B=Black W= White	See Options

Example: HS5-RGBAW-B-MNB

HS5-_____-_____-_____