



# PRISM PAR ZOOM

## RGBW Specification Sheet



5 Holt Drive,  
Stony Point, NY 10980  
845-947-3034  
info@tslight.com

### Control

- Protocol: USITT DMX-512
- DMX Channels: 5/7/9 or 11-channels
- Input: 3/5-pin XLR Male
- Output: 3/5-pin XLR Female
- Standalone, Master/Slave, Color Preset

### Power

- Voltage: 100-264VAC, 47-63 Hertz
- Power Consumption: 120W  
Max. Operating Temp.: 104°F (40°C) ambient

### Optics

- 36x 3W LEDs (R) 6PCS, G (8PCS), B (8PCS), A (6PCS), W (8PCS)
- 10-40 degree zoomable beam angle

### AnyFi™ Wireless DMX Receiver

- Frequency Hopping W-DMX™ Protocol
- 2.4Ghz ISM (2.402-2.48Ghz), 512 channels, 7 frequency groups
- Less Than 5ms Latency
- Receiver sensitivity: -94dBm

### Main Features

- 36x 3W R/G/B/A/W LEDs, 100,000 hours
- Built-in AnyFi™ wireless DMX receiver (wiCICLE 2.4Ghz or W-DMX™)
- Diffused Optical Lens
- Natural convection cooled, totally silent operation
- User selectable 32-bit dimming curves
- Variable electronic dimmer strobe
- Built-in color & chase macros via DMX
- Built-in auto programs in standalone and M/S
- Color mixing ability in standalone mode
- 10-40 degree zoomable beam angle
- User selectable 5/7/9 or 11-channel DMX modes
- LED control panel with 4\* touch sensitive buttons
- Control panel button lock/key
- 3/5-pin male input and 3/5-pin female output
- PowerCon™ compatible AC power In/Out connectors connectors

### Weight & Dimensions

- Dimensions: 10.7" (272.1 mm) x 5.7" (144 mm) x 11.2 inches (284.1 mm)
- Weight: 11.5 lbs. (5.2 kg)

### Mounting Options

- MNB** Clamp for pipe up to 2" OD
- CM4** Canopy for mounting to J-box
- USI** Unistrut mount
- STA** Controltrac adapter (2x)

### Ordering Matrix

Model	Array	Finish	Mounting
CRZ	RGBW	B - Black W - White	See Options

**Example:** CRZ-RGBW-B-MNB

CRZ-\_\_\_\_\_-\_\_\_\_\_-\_\_\_\_\_

\*Specification sheets are subject to change without notice.