



# PRISM PAR LE



5 Holt Drive,  
Stony Point, NY 10980  
845-947-3034  
info@tslight.com

## Features

- Variable white color temperature controlled via DMX or manually
- Zoom control via DMX or manually
- Color temperature presets (2800 to 10000 K)
- Built-in auto and custom programs recalled via DMX and Master/Slave
- 16-bit dimming of individual colors as well as master dimmer
- Five distinct dimming curves for programming versatility
- Color macros with included speed adjustment
- Double-bracket yoke doubles as a floor stand
- Neutrik® powerCON® power input/output connections
- 3-pin and 5-pin DMX input/output connections
- LED display with password protection

## Specifications

- **DMX Channels:** 3, 4, 5, 6, 7, 12 or 17
- **Data Connectors:** 3- and 5-pin XLR
- **Light Source:** 14 LEDs (Variable White)  
15 W, (985 mA), 50,000 hours life expectancy
- **Built-in Automated Programs:** Yes
- **Customizable Programs:** Yes
- **Recall Custom Programs:** Yes
- **Dimmer:** Electronic
- **Shutter/Strobe Rate:** Electronic
- **Strobe Rate:** 0 to 20 Hz
- **Standalone Color Mixing:** Yes
- **Color Temperature Presets:** Yes
- **Installed Optics:** Zoomable optics from 6° to 30°
- **Beam Angle:** 6° to 30°
- **Field Angle:** 11° to 43°
- **Zoom Angle:** 6° to 30°
- **Dimming Modes:** 9
- **Illuminance (6°):** 8,000 lux @ 5m
- **Illuminance (30°):** 695 lux @ 5m
- **Color Temperature (range):** 2800K to 10000K
- **IP Rating:** IP20, dry location
- **Cable Length:** 5 ft (1.5m)
- **Power Connection:** Edison plug to Neutrik® powerCON®
- **Power Input:** Neutrik® powerCON®
- **Power Output:** Neutrik® powerCON®
- **Power Linking:** 7 units @ 120V; 13 units @ 208V; 14 units @ 230V
- **Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)
- **Power and Current:** 205 W, 1.71 A @ 120 V, 60 Hz
- **Power and Current:** 208 W, 0.99 A @ 208 V, 60 Hz
- **Power and Current:** 212 W, 0.93 A @ 230 V, 50 Hz
- **Weight:** 17.8 lb (8.1 kg)
- **Dimensions:** 11.1 x 9.3 x 13.8 in (283 x 236 x 348 mm)
- **Approvals:** CE, MET

## Mounting Options

- MNB** Clamp for pipe up to 2" OD
- CM4** Canopy for mounting to J-box
- US1** Unistrut mount
- STA** Controltrac adapter (2x)

## Ordering Matrix

Model	Mounting
PRISMPARLE	See Options

**Example:** PRISM PAR LE-MNB

PRISMPARLE - \_\_\_\_\_