

Curved Track

1, 2, and 3 Circuit Systems



5 Holt Drive,
Stony Point, NY 10980
845-947-3034
info@tslight.com

- Supplied and ready for installation
- Can be bent as sections of a circle
- Conforms to the architecture of curved or arched ceilings/walls
- Track sections come in a maximum length of 6'
- 1-circuit track bends to a minimum radius of 7'
- 2 and 3-circuit track bends to a minimum radius of 8'
- Surface and pendant mounting available
- Comes in standard black, white and satin aluminum finishes


Curved Track Section

1-Circuit	CT1
2-Circuit	CT2
2-Circuit 277-Volt	CT277
3-Circuit	CT3

Add suffix B-Black; W-White; N-Natural Aluminum.


CT1

1-Circuit Track




CT2, CT277, CT3

2 & 3-Circuit Track



COMPONENTS




Used when energizing track from an outlet box. May require conduit adapter.

Adapter

	Regular	Mirror
1-Circuit XTSAJ 10	GES 11	GES 12
2-Circuit XTSAJ 10	TEK 11	TEK 12
2-Circuit 277V XTSAJ 10	HTEK 11	HTEK 12
3-Circuit XTSAJ 10	XTSA 11	XTSA 12


Add suffix B-Black; W-White.



Center Feed

Used to join two sections of track together in a straight line. May be used as a feed point.

	Black	White
1-Circuit	GES 14B	GES 14W
2-Circuit	TEK 14B	TEK 14W
2-Circuit 277-Volt	HTEK 14B	HTEK 14W
3-Circuit	XTSA 14B	XTSA 14W



Straight Connector

Used to join two sections of track together in a straight line.


	Black	White
1-Circuit	GES 21B	GES 21W
2-Circuit	XTSA 21B	XTSA 21W
2-Circuit 277-Volt	XTSA 21B	XTSA 21W
3-Circuit	XTSA 21B	XTSA 21W



J-Box Cover

Used to cover an outlet box.

	Black	White
1-Circuit	GES 15B	GES 15W
2-Circuit	GES 15B	GES 15W
2-Circuit 277-Volt	GES 15B	GES 15W
3-Circuit	GES 15B	GES 15W




End Cap

Used to end any open configuration of track.

	Black	White
1-Circuit	GES 41B	GES 41W
2-Circuit	XTSA 41B	XTSA 41W
2-Circuit 277-Volt	XTSA 41B	XTSA 41W
3-Circuit	XTSA 41B	XTSA 41W

COMPONENTS (Continued)



Reinforcement Plate

Used to further stabilize the joining of two pieces of track. Recommended for use with suspended installations.

	Black	White
1-Circuit	GEA 21B	GEA 21W



Bending Tool

Used after field cutting to bend the conductor ends to a 90° angle. Use the opposite end of the tool to measure the correct position of the bent conductors.

	Black
1-Circuit	XTSV 12
2-Circuit	XTSV 12
2-Circuit 277-Volt	XTSV 12
3-Circuit	XTSV 12


MOUNTING

Pendant Mount

Stem and canopy kit for mechanical and electrical suspension. Measures 1/4" for 1-circuit and 3/8" for 2 and 3-circuit. Standard lengths: 12", 18", 24", 36" and 48". Custom lengths available. Please consult factory.


	Length	Black	White
1 Ct.	12 in.	GEA 12B	GEA 12W
	18 in.	GEA 18B	GEA 18W
	24 in.	GEA 24B	GEA 24W
	36 in.	GEA 36B	GEA 36W
	48 in.	GEA 48B	GEA 48W
2 & 3 Ct.	12 in.	SPUS 12B	SPUS 12W
	18 in.	SPUS 18B	SPUS 18W
	24 in.	SPUS 24B	SPUS 24W
	36 in.	SPUS 36B	SPUS 36W
	48 in.	SPUS 48B	SPUS 48W

Custom lengths available.




End feed suspension bracket for mechanical and electrical connection to the track.

	Black	White
1-Ct.	GEA 4EB	GEA 4EW
2 & 3-Ct.	SP 4EB	SP 4EW



Point suspension bracket for mechanical connection to the track.

	Black	White
1-Ct.	GEA 4PB	GEA 4PW
2 & 3-Ct.	SP 4PB	SP 4PW



Center feed suspension bracket for mechanical and electrical connection to the track.

	Black	White
1-Ct.	GEA 4IB	GEA 4IW
2 & 3-Ct.	SP 4IB	SP 4IW

Suspension Mount

Cable kit with canopy. SKB-12 not included for 2 or 3-circuit systems, not available for 1-circuit systems.

	Length	Model #
Black	24 in.	CG 24B
	48 in.	CG 48B
	72 in.	CG 72B
White	24 in.	CG 24W
	48 in.	CG 48W
	72 in.	CG 72W

