



MR16

SORAA LED



5 Holt Drive,
Stony Point, NY 10980
845-947-3034
info@tslight.com

A classic styled fixture that features a 7.5W Soraa MR16 and accepts numerous accessories. The hinged front easily allows you to add accessories to the fixture and to add magnetic Snaps to the Soraa lamp.

By utilizing Soraa's Snap System, there are unlimited possibilities for customizing this fixture. Options include the ability to field change the beam angle (Beam Spreader Snap), alter color temperature (CTO Snap), or to add a louver. Color Snaps can be used to produce brilliant hues of any color that Rosco or Lee offer.

The Enhance Lens Snap can increase the vividness of warm colors (including red, orange and pink and greens). Aim Snaps can bend the beam to a maximum deflection angle of 20°. Linear Snap Lenses can alter the beam to act as a wall wash.

Manufactured in the USA - IBEW

PRODUCT LISTED
BY A NATIONALLY
RECOGNIZED
TESTING
LABORATORY



SORAA
Simply Perfect Light™

LED

- 10° SORAA lamp included - use snaps to change the beam angle.
- Color temp options: 2700K and 3000K
- CRI: 90 or 95
- No UV or IR

Dimming*


- Trailing edge (ELV)
- Leading edge (Triac)

Construction

- Powder coated steel with black, white or silver finish
- 0-180° tilt, 360° rotation
- Locking yoke
- Accepts accessories

Electrical

- Electronic driver
- 100-120V, 50/60Hz
- Meets FCC 47 CFR Part 15/18 Requirements



Features

- Use with electronic low voltage (ELV) Dimmer only (AKA Trailing Edge and Reverse Phase)
- Precision optics delivers high quality smooth gradient light beam patterns
- Industry leading lumen maintenance and color point stability
- Snap lenses provide numerous customization options including adding color
- 120/277V AC
- Power factor 0.92
- Dimmable with forward and reverse phase dimmers
- Internal self-locking yoke
- Numerous mounting options

Lamp Type	Watts	CRI	Lumens*
Brilliant	7.5	90 (R9=0)	600
Vivid	7.5	95 (R9=95)	410

* Lumens vary depending on color temperature – results for 3000K lamp used above


Ordering Matrix

Model	CRI	Color Temperature	Color	Mounting Options	Accessories
LEDI020	90 95	27 = 2700K 30 = 3000K 40 = 4000K*	B = Black W = White S = Silver CC = Custom Color	See Mounting Options	See Accessory Options

* Only available at 95 CRI.

Example: LEDI020-95-27-B-ADI-00325

LEDI020-_____-_____-_____-_____-_____




Snap Lenses


* Specification sheets are subject to change without notice.

Photometric Data


20° Beam, 3000°K




25° Beam, 3000°K



36° Beam, 3000°K



60° Beam, 3000°K




Mounting Options


ADI Track Adapter for commercial grade 1-circuit track. 120V. For use with lightweight fixtures.

TA2 Track adapter for G-Series specification grade 2-circuit track. 120V.

HTA2 Track adapter for G-Series specification grade 2-circuit track. 277V.




CMI Canopy Mount




US1 6⁵/₈" x 1¹/₂" Unitrut Adapter




TB4 6¹/₄" Portable wall mount/table base floor, wall or table use.



MC Light duty pipe clamp for small fixtures. For pipes up to 15/16" O.D.



MN Medium duty pipe clamp for small to large fixtures. For pipes up to 2" O.D.



Accessories

00325	25° Beam Spreader Snap
00327	36° Beam Spreader Snap
00329	60° Beam Spreader Snap
00331	10°-25° Linear Snap
00333	10°-36° Linear Snap
03259	10°-60° Linear Snap
00335	25°X25° Flat Top Snap
00337	36°X36° Flat Top Snap
00339	40° Cutoff Louver
00325	20° Maximum Deflection Snap
00323	¼ Color Temperature Shift Snap
00321	½ Color Temperature Shift Snap
00319	¾ Color Temperature Shift Snap
02183-C	Color Snap (Specify Color)
03281	Enhance Snap

Fixture Accessories

LV3	Louwer
XL3	Cross Baffle Louwer
BD3	Barndoor
HD3	Hood
SH3	Sparkle Hood
GF3	Glass Color Filter
DF3	Dichroic Color Filter
GF3-600	5°x50° Linear Lens
GF3-601	Beam Softener
GF3-673	50°x50° Spread Lens
CC18	Coiled Cord
SC-24	Safety Cable
WL	Wrench Locking

Extension Wands

SP 12	12" Stem
SP 18	18" Stem
SP 24	24" Stem
SP X	Custom Length

Finish

B	Black
W	White
S	Silver
CC	Custom Color

IES Files

Visit tslight.com to find comprehensive IES data.